



ALUMINUM ELECTROLYTIC CAPACITORS

LK series RADIAL LEAD TYPE

* STANDARD CASE SIZES AND PERMISSIBLE RIPPLE CURRENT

D XL (MM)

Cap(*F)	W.V. Code	6.3		10		16		25		35		50	
		OJ		1A		1C		1E		1V		1H	
0.1	R10											5x11	1.1
0.15	R15											5x11	1.6
0.22	R22											5x11	2.3
0.33	R33											5x11	3.5
0.47	R47											5x11	5.0
0.68	R68											5x11	7.3
1	O10											5x11	10.7
1.5	1R5											5x11	16
2.2	2R2											5x11	23
3.3	3R3											5x11	40
4.7	4R7							5x11	45			5x11	45
6.8	6R8							5x11	55			5x11	55
10	100					5x11	55	5x11	70			5x11	70
15	150					5x11	70	5x11	85	5x11	85	5x11	95
22	220					5x11	85	5x11	100	5x11	100	5x11	110
33	330					5x11	100	5x11	140	5x11	140	6.3x11	165
47	470			5x11	110	5x11	140	5x11	170	6.3x11	190	6.3x11	190
68	680	5x11	150	5x11	150	5x11	160	5x11	230	6.3x11	230	6.3x11	250
100	101	5x11	180	5x11	180	6.3x11	230	6.3x11	280	8x12	300	8x12	320
150	151	6.3x11	250	6.3x11	250	8x12	280	8x12	370	10x12	400	10x16	420
220	221	6.3x11	310	6.3x11	310	8x12	370	8x12	400	10x12	440	10x16	490
330	331	6.3x11	400	8x12	400	8x12	420	10x12	490	10x16	550	13x21	600
470	471	8x12	390	8x12	530	10x12	550	10x16	660	10x20	840	13x21	760
1000	102	10x12	650	10x16	810	10x16	910	13x21	1010				
2200	222	13x21	1060	13x21	1200	13x21	1300						
3300	332	13x25	1270	13x25	1420	16x25	1550						•

MAXIMUM RIPPLE CURRENT(mA rms/105*,120Hz)