



ALUMINUM ELECTROLYTIC CAPACITORS

Ripple Current(mA r.m.s./105*,100kHz)

Rated voltage 10V(1A)				
Nominal capacitance(*F)	Size *D x L(mm)	Ripple Current	Impedance *(MAX)	
			20*, 100kHz	-10*, 100kHz
100	5x11	210	0.58	1.21
220	6.3x11	340	0.22	0.50
470	8x11.5	640	0.13	0.29
680	8x16	840	0.087	0.19
1000	8x20	1050	0.069	0.15
680	10x12.5	865	0.080	0.16
1000	10x16	1210	0.060	0.13
1200	10x20	1400	0.046	0.10
1500	10x23	1650	0.042	0.096
2200	10x28	1910	0.031	0.074
1500	13x16	1450	0.049	0.107
2200	13x20	1900	0.035	0.080
3300	13x25	2230	0.027	0.056
3900	13x30	2650	0.024	0.052
4700	13x35	2880	0.020	0.046
5600	13x40	3350	0.017	0.039
2200	16x16	1940	0.042	0.088
3900	16x20	2530	0.027	0.062
5600	16x25	2930	0.021	0.048
6800	16x31.5	3450	0.017	0.035
8200	16x35.5	3610	0.015	0.034
10000	16x40	4080	0.013	0.028
2700	18x16	2210	0.043	0.09
5600	18x20	2860	0.026	0.054
6800	18x25	3140	0.019	0.043
8200	18x31.5	4170	0.015	0.033
10000	18x35.5	4220	0.014	0.032
12000	18x40	4280	0.012	0.025