



ALUMINUM ELECTROLYTIC CAPACITORS

Ripple Current(mA r.m.s./105*,100kHz)

Rated voltage 25V(1E)				
Nominal capacitance(*F)	Size *D x L(mm)	Ripple Current	Impedance *(MAX)	
			20*, 100kHz	-10*, 100kHz
47	5x11	210	0.58	1.21
100	6.3x11	340	0.22	0.50
220	8x11.5	640	0.13	0.29
330	8x16	840	0.087	0.19
470	8x20	1050	0.069	0.15
330	10x12.5	865	0.080	0.16
470	10x16	1210	0.060	0.13
680	10x20	1400	0.046	0.10
820	10x23	1650	0.042	0.096
1000	10x28	1910	0.031	0.074
680	13x16	1450	0.049	0.107
1000	13x20	1900	0.035	0.080
1500	13x25	2230	0.027	0.056
1800	13x30	2650	0.024	0.052
2200	13x35	2880	0.020	0.046
2700	13x40	3350	0.017	0.039
1000	16x16	1940	0.042	0.088
1800	16x20	2530	0.027	0.062
2700	16x25	2930	0.021	0.048
3300	16x31.5	3450	0.017	0.035
3900	16x35.5	3610	0.015	0.034
4700	16x40	4080	0.013	0.028
1200	18x16	2210	0.043	0.09
2200	18x20	2860	0.026	0.054
3300	18x25	3140	0.019	0.043
3900	18x31.5	4170	0.015	0.033
4700	18x35.5	4220	0.014	0.032
5600	18x40	4280	0.012	0.025