



ALUMINUM ELECTROLYTIC CAPACITORS

Ripple Current(mA r.m.s./105*,100kHz)

Rated voltage 35V(1V)				
Nominal capacitance(*F)	Size *D x L(mm)	Ripple Current	Impedance *(MAX)	
			20*, 100kHz	-10*, 100kHz
33	5x11	210	0.58	1.21
56	6.3x11	340	0.22	0.50
150	8x11.5	640	0.13	0.29
220	8x16	840	0.087	0.19
270	8x20	1050	0.069	0.15
220	10x12.5	865	0.080	0.16
330	10x16	1210	0.060	0.13
470	10x20	1400	0.046	0.10
560	10x23	1650	0.042	0.096
680	10x28	1910	0.031	0.074
470	13x16	1450	0.049	0.107
680	13x20	1900	0.035	0.080
1000	13x25	2230	0.027	0.056
1200	13x30	2650	0.024	0.052
1500	13x35	2880	0.020	0.046
1800	13x40	3350	0.017	0.039
680	16x16	1940	0.042	0.088
1200	16x20	2530	0.027	0.062
1800	16x25	2930	0.021	0.048
2200	16x31.5	3450	0.017	0.035
2700	16x35.5	3610	0.015	0.034
3300	16x40	4080	0.013	0.028
1000	18x16	2210	0.043	0.09
1800	18x20	2860	0.026	0.054
2200	18x25	3140	0.019	0.043
2700	18x31.5	4170	0.015	0.033
3300	18x35.5	4220	0.014	0.032
3900	18x40	4280	0.012	0.025