



ALUMINUM ELECTROLYTIC CAPACITORS

Ripple Current(mA r.m.s./105*,100kHz)

Rated voltage 50V(1H)				
Nominal capacitance(*F)	Size *D x L(mm)	Ripple Current	Impedance *(MAX)	
			20*, 100kHz	-10*, 100kHz
22	5x11	180	0.70	1.54
56	6.3x11	295	0.30	0.63
100	8x11.5	555	0.17	0.39
120	8x16	730	0.12	0.28
180	8x20	910	0.091	0.19
150	10x12.5	760	0.12	0.26
220	10x16	1050	0.084	0.19
270	10x20	1220	0.060	0.14
330	10x23	1440	0.055	0.115
470	10x28	1690	0.043	0.094
270	13x16	1260	0.061	0.140
470	13x20	1660	0.045	0.099
560	13x25	1950	0.034	0.071
680	13x30	2310	0.030	0.066
820	13x35	2510	0.025	0.057
1000	13x40	2920	0.021	0.044
470	16x16	1690	0.055	0.126
820	16x20	2210	0.034	0.081
1000	16x25	2555	0.025	0.057
1200	16x31.5	3010	0.022	0.052
1500	16x35.5	3150	0.019	0.047
1800	16x40	3710	0.016	0.036
560	18x16	1930	0.054	0.118
1000	18x20	2490	0.036	0.086
1200	18x25	2740	0.026	0.059
1800	18x31.5	3635	0.021	0.048
2200	18x35.5	3680	0.017	0.040
2700	18x40	3800	0.014	0.032