



ALUMINUM ELECTROLYTIC CAPACITORS

Ripple Current(mA r.m.s./105*,100kHz)

Rated voltage 25V(1E)				
Nominal capacitance(*F)	Size *D x L(mm)	Ripple Current	Impedance *(MAX)	
			20*, 100kHz	-10*, 100kHz
47	5x11	250	0.30	1.0
100	6.3x11	405	0.13	0.41
220	8x11.5	760	0.072	0.22
330	8x16	995	0.056	0.17
470	8x20	1250	0.041	0.13
330	10x12.5	1030	0.053	0.16
470	10x16	1430	0.038	0.12
680	10x20	1820	0.023	0.069
820	10x23	2150	0.022	0.066
1000	13x20	2360	0.021	0.053
1500	13x25	2770	0.018	0.045
1800	13x30	3290	0.016	0.041
2200	13x35	3400	0.015	0.039
1800	16x20	3140	0.018	0.045
2700	16x25	3460	0.016	0.043

Ripple Current(mA r.m.s./105*,100kHz)

Rated voltage 35V(1V)				
Nominal capacitance(*F)	Size *D x L(mm)	Ripple Current	Impedance *(MAX)	
			20*, 100kHz	-10*, 100kHz
33	5x11	250	0.30	1.0
56	6.3x11	405	0.13	0.41
150	8x11.5	760	0.072	0.22
220	8x16	995	0.056	0.17
270	8x20	1250	0.041	0.13
220	10x12.5	1030	0.053	0.16
330	10x16	1430	0.038	0.12
470	10x20	1820	0.023	0.069
560	10x23	2150	0.022	0.066
680	13x20	2360	0.021	0.053
1000	13x25	2770	0.018	0.045
1200	13x30	3290	0.016	0.041
1500	13x35	3400	0.015	0.039
1200	16x20	3140	0.018	0.045
1800	16x25	3460	0.016	0.043