



ALUMINUM ELECTROLYTIC CAPACITORS

SS series RADIAL LEAD TYPE

* STANDARD CASE SIZES AND PERMISSIBLE RIPPLE CURRENT

D XL (MM)

Cap(*F)	W.V. Code	6.3	6.3	10	16	25	35	50
		OJ	OJ	1A	1C	1E	1V	1H
0.1	R10							4x7
								1.0
0.22	R22							4x7
								2.3
0.33	R33							4x7
								3.5
0.47	R47							4x7
								5.0
1	O10							4x7
								10
2.2	2R2							4x7
								19
3.3	3R3							4x7
								24
4.7	4R7							4x7
								23
10	100					4x7	4x7	6.3x7
						28	31	38
22	220			4x7	4x7	5x7	5x7	6.3x7
				35	39	48	52	58
33	330	4x7	4x7	4x7	5x7	5x7	6.3x7	
		33	40	43	44	58	65	
47	470	4x7	4x7	4x7	5x7	6.3x7	8x7	
		39	48	59	65	71	85	
100	101	5x7	5x7	6.3x7	6.3x7	8x7		
		65	78	87	98	115		
220	221	6.3x7	6.3x7	6.3x7	8x7			
		110	120	145	168			
330	331	8.7	8.7					
		165	180					
470	471	8x7						
		240						

MAXIMUM RIPPLE CURRENT(mA rms/85*,120Hz)