



ALUMINUM ELECTROLYTIC CAPACITORS

MS / MX series RADIAL LEAD TYPE

* STANDARD CASE SIZES AND PERMISSIBLE RIPPLE CURRENT

D XL (MM)

Cap(*F)	W.V. Code	4		6.3		10		16		25		35		50	
		OG		OJ		1A		1C		1E		1V		1H	
0.1	R10													•4x5	1
0.22	R22													•4x5	2.5
0.33	R33													•4x5	4
0.47	R47													•4x5	6
1	O10													•4x5	8.6
2.2	2R2											•4x5	9	•4x5	9.1
3.3	3R3									•4x5	11	•4x5	12	4x5	13
4.7	4R7							•4x5	11	•4x5	13	4x5	14	5x5	20
10	100			•4x5	14	•4x5	16	•4x5	18	5x5	27	5x5	27	6.3x5	31
22	220	•4x5	20	•4x5	22	5x5	30	5x5	35	6.3X5	46	6.3x5	46		
33	330	4x5	27	5x5	34	5x5	45	6.3X5	51	6.3x5	54				
47	470	4x5	37	5x5	37	6.3X5	50	6.3x5	65	6.3x5	65				
100	101	5x5	62	6.3X5	62	6.3x5	80								
220	221	6.3X5	74												

Size 3 x 5 is available for capacitors marked, " • "is MX series
 MAXIMUM RIPPLE CURRENT(mA rms/85*,120Hz)